

## GRO IPE TILES

GRO IPE Wood Deck Tiles are structural deck tiles designed to be used with fixed and adjustable height pedestals on both flat and sloped roof decks, terraces, plazas, or patios. IPE is one of the most commonly used South American hardwoods for outdoor decking. When accompanied with GRO Fasteners, the deck tiles can be locked down to the pedestals to mitigate wind uplift and to create a secure system. Alternatively, GRO IPE Wood Deck Tiles can also be laid over existing concrete or decks using fixed height spacer shims to lift the tiles off the surface and to ensure good drainage. GRO IPE Wood Tiles can be FSC®-C108155 certified upon request and GRO is a FSC® certified company.



MATERIAL / BOTANICAL NAME	Ipe / Tabebuia sp.
DIMENSIONS	24" x 24" x 1 5/8" (nominal); 23 7/8" x 23 7/8" x 1 1/2" (actual) 24" x 48" x 1 5/8" (nominal); 23 7/8" x 47 7/8" x 1 5/8" (actual) Custom sizes also available
WEIGHT	24" x 24" = 23.5 lbs; 24" x 48" = 48.5 lbs.
COLOR / GRAIN	Typically reddish brown color, but can vary from olive brown to blackish, with lighter or darker striping Fine to medium texture, grain always interlocked
SURFACE FINISH	Ends waxed with paraffin, slats with machined finish, and wood not coated with oil
DURABILITY / RATING	Class A
HARDNESS (JANKA)	3680 (very hard)
CHARACTERISTICS	Resists termites, fire, decay and mold Wear and scuff resistant Resists bending, shearing, warping & twisting Weathers without splintering Low maintenance Not resistant to marine borers
ACCOMPANYING GRO PRODUCTS	GRO PEDESTALS, GRO FASTENING KIT

