


## GRO WOOD DECK TILE FASTENING KITS

GRO Fastening Kits for use with GRO Wood Deck Tiles provide a secure connection between pedestals and the finished deck surface. The weight of the deck pavers create a monolithic system to hold the system in place and mitigate against wind uplift. GRO offers 2 fastening kit options for wood deck tile projects; choice of fastening kit is based on pedestal heights.

### SCREW & WASHER



**For pedestal heights > 2.5"**


**Easily removable for repairs and maintenance**

GRO Wood Deck Tiles are engineered with a slot cut in each corner enabling a special washer and finishing screw to be inserted. Once all tiles are in place, the washer and screw are invisibly screwed into the corresponding top of the pedestal to "lock down" the tiles, ensuring a safe, secure, and level surface. Our fastening kit makes removal of a centrally-located tile simple, and eliminates the need to remove all tiles from the perimeter up to that point.

**Fastening kit pedestal height < 2.5" installation:**

Three wooden deck tiles are placed on a pedestal. The screw and washer is placed into the fastening slot of each wood deck tile. The fourth deck tile is placed on the pedestal and the screw is fastened down to lock the wood deck tiles in place.

### PLASTIC PINS



**For pedestal heights < 2.5"**

**More permanent connection**

GRO Wood Deck Tiles have a connection hole in the bottom corners of the pavers to secure a plastic pin which provides a connection to the pedestals. Once all tiles are in place, the plastic pins are invisible, and ensure a safe, secure, and level surface. With our plastic pin fastening kit, removal of tiles for repairs and maintenance is simple and straightforward.

**Fastening kit pedestal height < 2.5" installation:**

Align the holes on the underside of the wood deck tiles with the plastic pins in the pedestals. Push down on tiles until connection is complete.